

and the second second

NEW AGE OF HVAC SYSTEMS

New **HVAC** Systems



Hispacold is a company with over 45 years of experience leading in the passenger transport HVAC sector.

- > HVAC SYSTEMS OPERATING IN MORE THAN
 100 COUNTRIES ACROSS THE 5 CONTINENTS.
- > ON BOARDED OWN TECHNOLOGY.
- > JOINT INNOVATION WITH TOP-LEVEL UNIVERSITIES AND TECHNOLOGY CENTERS.
- > SEVERAL PATENTS REGISTERED.
- CERTIFIED MANAGEMENT SYSTEMS FOR QUALITY, ENVIRONMENT AND OCCUPATIONAL HEALTH AND SAFETY: EN 15085-2, ISO/TS 22163:2017 (IRIS), ISO 9001:2015 ENAC, ISO 14001:2015 ENAC AND OHSAS 18001:2007 ENAC.

Design, manufacturing and sales of HVAC systems and components for fuel, hybrid and electric buses and coaches and for rail vehicles, for any type of climate conditions.

NEW AGE OF HVAC SYSTEMS

NEW PRODUCT RANGE

- > HIGHLY EFFICIENT
- > SUSTAINABLE

C hispacold

- > POWER RANGE
- > MINIMUM WEIGHT AND REDUCED FOOT PRINT
- > EASE INSTALLATION
- > FREE COOLING 0-100%
- > ADAPTABLE TO ANY TYPE OF VEHICLES
- > MINIMUM REFRIGERANT CHARGE
- > GWP <150 GASES

The new range of HVAC systems covers:

Electromobility, City and Intercity buses.











All climate and/or environmental zones.





BREEZE RANGE









A new wave of HVAC





Breeze range

HVAC SYSTEMS

DESIGN · POWER · SUSTAINABILITY

- > INNOVATIVE MATERIALS
- > NEW DESIGN
- > 60% LESS REFRIGERANT CHARGE
- > MINIMUM WEIGHT AND FOOT PRINT
- > EASE INSTALLATION
- > AIR EXTRACTION
- > SUITABLE FOR ANY TYPE OF VEHICLES
- > MECHANICAL FIXATION
- > FREE COOLING 0-100%
- > WATER OR PTC BACK UP HEAT
- > REVERSIBLE HEAT PUMP FOR EBREEZE



Breeze

FOR ELECTRIC VEHICLES **eBreeze**

	100	200	300	100e / 100e HP	200e / 200e HP
Vehicle type		Fuel		Electric / Electric with H	leat Pump / Hydrogen
Listed cooling capacity (kW) ¹	28 / 32 / 34	38 / 41 / 44	46	22	29
Rated cooling capacity (kW) ²	18 / 21 / 23	25 / 27 / 30	34	16	21
Heating capacity (kW) ³	35	49	36	27	30
Evaporator air capacity (m ³ /h) ⁴	5160	7740	10320	5160	7740
Fresh air intake range (%)	0-100	0-100	0-100	0-100	0-100
Dimensions $W^5 x L x H$ (mm)	2000x1950x215	2000x2550x215	2000x2550x215	2000x2450x380	2000x3050x380
Average filling volume R134a (kg) ⁶	1,9	2,2	2,4	2,6	3,5
Weight (kg) (without and with heating and fresh air intake)	91-97	128-135	134-142	162-164 / 167-169	210 / 215
Weight with Inverter				221	276

-

1 Conditions 40°C/40°C/95%

2 Conditions 35°C/27°C/19°C

3 Conditions -20°C/+80°C 16,7 l/min

4 Free blow with brushless motors

5 Width varie according to the radii of vehicles roof between 2000-2020 mm

6 All systems available with R513A and other refrigerants with GWP<150.

Back up heat with PTC or Hot water

Estimate system capacity with heat pump.







Naturally efficient





EN range

ELECTRICAL HVAC SYSTEMS

ECOLOGICAL · EFFICIENT · SILENT

- > HIGH PERFORMANCE
- > EQUIPPED WITH DRIVER HVAC
- > OPTIMAL EFFICIENCY AT PARTIAL CHARGE
- > HIGHLY RELIABLE
- > FREE COOLING 0-100%
- > PTC OR WATER BACK UP HEAT
- > WIDELY TESTED IN THE MARKET
- > NOISELESS

hiso

- > ZERO EMISSIONS
- > DEHUMIDIFICATION FUNCTION
- > REVERSIBLE HEAT PUMP



	9EN 1C	12EN 1C
Cooling capacity (kW)	28	36
Heating capacity (kW)	30	44
Dimensions (mm)	2097 x 1962 x 432	2695 x 1962 x 432
Weight (kg)	240	300
Heat pump capacity (kW)	14	18

ACCESSORIES FOR ELECTRIC VEHICLES



BTMS

Thermal conditioning of electric batteries for opportunity charge and night charge.



- > OPPORTUNITY CHARGE AND NIGHT CHARGE
- > PLUG AND PLAY
- > HEATING OPTIONAL
- > RELIABILITY
- > INDEPENDENT FROM THE HVAC UNIT
- > J1939 CAN COMMUNICATION
- > INDEPENDENT CONTROL
- > ADAPTABLE SOLUTIONS

hispacold.es







Cooling of engines and other electrical components in the power train.



- > SELF-CLEANING
- > BRUSHLESS MOTORS
- > CUSTOMIZABLE
- > J1939 CAN COMMUNICATION
- > INDEPENDENT CONTROL

CONTROL PANELS



Ecomaster range

High range of automatic controls.

Regulate passengers and drivers comfort inside the vehicle.



- > FOR DIESEL, GAS AND HYBRID VEHICLES
- > DUAL ZONE CLIMATE CONTROL
- > ECO MODE FUNCTION TO SAVE FUEL AND ENERGY
- > AUTOMATIC OR MANUAL CONTROL AVAILABLE
- > 2 X CAN COMMUNICATION
- > SELF-DIAGNOSIS
- > USB INPUT FOR EASY SOFTWARE UPDATE AND **DATA LOGGER FUNCTION**

Temperature regu	lation needs	Ecomaster range
Air conditioning for passengers	ڧ ڧ ڧ ڧ ڧ	BASIC BASIC DOUBLE DECKER
Heating for the driver	<i>ݔ</i> ݭݔݭݔ	BASIC DS BASIC DHA
HVAC for passengers	ڧڧڧڧڧ	
HVAC for driver	ݔݔݔݔݧݔ <u></u>	
Driver and passengers comfort	ݩݭݭݭݭ	COMFORT RICOMFORT
Any other climate settings		

hispacold.es



NS

netiOs range

New range control panels. **Total HVAC control.** Chis AUTO / OFF AUTO / OFF MENU

- > FOR ALL VEHICLES SINGLE-DECKER, DOUBLE-DECKER, ARTICULATED, **TROLLEY, DIESEL, GAS, HYBRID, ELECTRIC**
- > CUSTOMIZABLE INTERFACE ACCORDING TO **CUSTOMER'S NEEDS AND BRAND IMAGE**
- > HIGH FLEXIBILITY TO OFFER A SOLUTION FOR ANY CLIMATE CONTROL CONFIGURATION **DUAL ZONE, SINGLE ZONE, ONLY HEATING OR COOLING, COMPLETE CLIMATE**
- > ECO MODE FUNCTION TO SAVE FUEL **AND ENERGY**
- > AUTOMATIC OR MANUAL CONTROL AVAILABLE
- > COMPATIBLE WITH MULTIPLEXED SYSTEMS
- > 2 X CAN AND 1 X LIN COMMUNICATION
- > SELF-DIAGNOSIS AND UDS COMPATIBLE
- > USB INPUT FOR EASY SOFTWARE **UPDATE AND DATA LOGGER FUNCTION**

Temperature regulation needs

netiOS range

Air conditioning for passengers	فرفر فرفر فرف		
Heating for the driver	ݩݛݩݛݩݛݩݛݩݛ ݩ		Total HVAC control
HVAC for passengers	<i>ݩ</i> ݥݩݥݩݥ		نرنزن فر 🕻
HVAC for driver	<i>ڧ</i> ەنيەنى نەن نەن ئە		×`\\` ₩
Driver and passengers comfort	ڣ۫ڣ۬ڣڣڣڣڣ	Алто лога (Алто	
Any other climate settings			

COMPRESSORS

550 CC and 660 CC compressors

Increased power and performance in minimum space.



- > HIGHLY RELIABLE AND EFFICIENT
- > ELECTROMAGNETIC CLUTCH FOR HIGH-REQUIMENT APPLICATIONS
- > DEVELOPED BY HISPACOLD
- > LOW NOISE AND VIBRATION LEVELS
- > LESS LUBRICANT
- > HIGHLY COMPACT

hispacold.es



COMPONENTS







eCo3 air purifier

- > Eliminates bad odors.
- > Neutralizes bacteria, viruses, fungus, allergens and germs in general.
- Increases the oxygen concentration to prevent the air from becoming contaminated.
- > Reduces feelings of tiredness for the driver.
- > Reduces feelings of motion sickness and nausea for passengers.
- > Acts on suspended particles.
- > Eliminates some chemical pollutants.
- > Compatible with vehicles that are already operating.

Heating station

- Regulates the flows of heating water through the different circuits in the vehicle.
- > Easy assembly and maintenance.
- Versatility: adaptable to any heating configuration with simple modifications.
- > Its geometry minimizes losses and optimizes heating flows.

Driver HVAC unit

- > High capacity with a reduced size.
- > Defogs the front windshield in a very short time.
- > Can reach the desired temperature in the driver's compartment.
- > Fresh air intake and fillers to get excellent air quality
- > Windscreen-feet flaps to optimize air distribution.
- > Available with options for heating, heating + air conditioning, and manual or motorized water valve.

INTEGRATED SYSTEMS



Compressor, evaporator and condenser integrated in vehicle

- Reduced weight.
- Optimized cost.
- > No visual impact.
- > Takes no space on the roof.
- > Safe maintenance without live line

The legacy of tomorrow

Strategic contribution to the Sustainable Development Goals (SDGs)

hispacold

NEW HISPACOLD FACILITIES

Free Trade Zone port SEVILLA SPAIN

36,000 m²



Hispacold has develope passenger transportatio 2030 Agenda and str



Use of natural refrigerants (R



Signum the brain of maintenance



Hispacold is working on designing a predictive maintenance and energy efficiency system based on **Artificial Inteligence.**







hispacold.es

antile coments